

CHRONOSWISS

MODERN MECHANICAL



TECHNICAL DATA

Model	PULSE GMT Frosted Guilloche Gold
Reference	CH-4221RM-GR
Display	Display: Center – minutes and seconds. Local Hour Counter: at 3 o'clock. GMT / 24-Hour Counter: at 9 o'clock, indicating the second time zone.
Case	Solid 26-piece, 5N Gold (48g), satin finish & sandblasted, partly polished bezel with partial knurling and curved, double coated anti-reflective sapphire crystal, screw-down case back with satin finish and sapphire crystal, onion crown, water resistance up to 5 bar, strap holders screwed down.
Measurements	Ø 41 mm, Height 13 mm, Lug to Lug: 46.27mm, Lug Width: 23mm
Movement	Chronoswiss Manufacture Caliber C. 6002, Automatic
Diameter	Ø 33.4 mm
Jewels	29
Balance Wheel	Glucydur, three-legged
Balance spring	Nivarox 1
Fine Adjustment	via Excenter
Shock protection	Incabloc
Frequency	4 Hz., 28 800 A/h (semi-oscillations)
Power reserve	55 hours
Special features	Skeletonized rotor made of tungsten, ball bearing; armature, escape wheel and screws polished; bridge with Geneva cut, ruthenium plated
Dial	Dial Construction: 3-dimensional dial construction brass. Center hand guilloché with frosted sandblasting finish, nickel galvanic coating. Hour Indicators: domed brass, sandblasted with nickel galvanic coating and black print. Dividing Ring: raw sandblasted brass with Chronoswiss logo printed in black. Dividing Line: polished. Minute Ring: fine sandblasted brass with black printed minute scale. Appliques: polished blue PVD-coated appliques. Screws: blued steel.
Hands	Steel polished & blued, Hand shape „Pyramid“
Strap	Integrated Rubber black, Chronoclap buckle Stainless Steel DLC coated black / 5 N Gold (2,5g)
Limited Edition	50